

ATLANTIC TM 775 FMG

DESCRIPTION

ATLANTIC 775 FMG is a multi-purpose semi-synthetic, non melting grease designed for general lubrication in food processing facilities. ATLANTIC 775 FMG is truly a multi-service, maintenance grease. Due to its excellent film forming characteristics and anti-wear qualities it will stay on the metal surfaces much longer than most conventional greases on the market today, resulting in longer lasting lubricity, with fewer lubrication intervals.

ATLANTIC 775 FMG is white, odorless, tasteless and is NSF/U.S.D.A. H-1 *Registered, which gives it full acceptability for use in all areas where incidental food contact may occur.

USAGE

ATLANTIC 775 FMG, with its semi-synthetic base oils and polymer additives, is completely resistant to water washout, friction and chemical attack. This makes ATLANTIC 775 FMG the Professional's Choice for all conveyor bearings, ball bearings, journal bearings, roller bearings, universal joints and all other lubrication points having sliding or rolling friction requiring a multi-purpose NSF/U.S.D.A. H-1 *Registered grease.

ADVANTAGES

! NSF/U.S.D.A. H-1 *REGISTERED ! REDUCES FRICTION & WEAR
! EXTREMELY WATER RESISTANT ! HIGH FILM STRENGTH
! NON-MELTING **! PREVENTS RUST & CORROSION**

*NSF H-1 Registration No. 059320

PACKAGE AVAILABILITY

Convenient disposable gun loader 14oz.
Cartridge
5-gal. Pail, 15-gal. Keg and 55-gal. Drum



TYPICAL SPECIFICATIONS

DESCRIPTION: ATLANTIC Product: 775 FMG

Color: White
Base Oil: Semi-Synthetic
Thickener: Synthetic
Texture: Buttery
USDA /NSF Rating: H-1

<u>TEST METHOD</u>	<u>ASTM METHOD</u>	<u>RESULTS</u>
N.L.G.I. Grade	----	2
Worked Penetration	D-217	280
Base Oil Viscosity, SUS @ 100°F	D-216	801
SUS @ 210°F	D-216	78.3
cSt @ 100°C	D-445	15.1
cSt @ 40°C	D-445	173
Pour Point, °F (°C)	D-97	10 (-12)
Flash Point, °F (°C)	D-92	400 (204)
Dropping Point, °F (°C)	D-566	NONE
Corrosion Preventative Test	D-1743	PASS
Timken OK Load, lbs.	D-2509	30