

ATLANTIC™ GOLD KING

EXTRA HEAVY-DUTY

ANTI-SEIZE COMPOUND

DESCRIPTION

ATLANTIC GOLD KING is an "Extreme Service" anti-seize and lubricating compound. Formulated with high concentrations of micro-size copper flakes, finely powdered zinc, and graphite; homogenized into an extremely water resistant, high temperature grease base. ATLANTIC GOLD KING provides the maximum protection to all threaded connections, particularly under severe stress conditions.

USAGE

ATLANTIC GOLD KING is particularly effective for use when dealing with fine-threaded connections in high heat and torque situations. ATLANTIC GOLD KING also provides extreme protection for rotary shouldered connections of drill collars, tool joints, and down-hole specialty tools. ATLANTIC GOLD KING reduces ft.-lb. torque on break-outs.

SERVICE RATING

0F (-18C) to 1500F (816C)

OPERATING RANGE

Base grease provides lubrication to 450F (232C). Metallic and lubricating solids provide lubrication to 1900F (1037C).

TYPICAL SPECIFICATIONS

<u>TEST</u>	<u>ASTM TEST METHOD</u>	<u>RESULTS</u>
Base Thickener	-----	Synthetic
Worked Penetration	D-217	290-310
Dropping Point, F	D-566	None
Base Oil Viscosity,		
SUS @ 100F	D-445	994
SUS @ 210F	D-445	67
Flash Point, F	D-92	450
Pour Point, F	D-97	0
Brushability (Minimum), F	-----	10

PACKAGE AVAILABILITY

1 gal. Pail, 2 gal. Pail
3 1/2 gal. Pail and 5 gal. Pail