

# **ATLANTIC™ NO. 3**

## **GENERAL PURPOSE VALVE LUBRICANT & SEALANT**

### **DESCRIPTION**

*ATLANTIC No. 3 VALVE LUBRICANT is a totally synthetic valve lubricant and sealant that contains no graphite, molybdenum disulfide, or other fillers. The broad temperature range and multi-service applications have found wide acceptance in the petrochemical industry.*

### **USAGE**

*ATLANTIC No. 3 is designed for use in all lubricated valves in hydrocarbon, L.P.G., aromatics, natural gas, aqueous solutions, water, acids, caustics and many other services.*

### **ADVANTAGES**

- M Broad Serviceability Range
- M 100% Synthetic, contains no soaps or clays
- M Will not dry out or harden in valve
- M Economical, does the work of several valve lubricants

### **TYPICAL SPECIFICATIONS**

Color Amber  
Texture Tenacious and Smooth  
Service Temperature 0 F to 500 F  
Dropping Point None  
Base Oils and Thickener Synthetic  
Special Additive Sub-Micron PTFE

### **PACKAGE AVAILABILITY**

5 qt. Cans, 5 gal. Pails, and 15 gal. Kegs  
J & K gun size Sticks  
Small Sticks for screw type lubricators