

ATLANTIC™ No. 2 H.D. PTFE SEALANT AND LUBRICANT

DESCRIPTION

ATLANTIC No.2 H.D. is a highly versatile valve sealant and lubricant that contains a balanced blend of fine to coarse PTFE particles suspended in a special synthetic lubricating carrier. ATLANTIC No.2 H.D. is resistant to a large variety of line products such as water, crude or heating oils, fuels, dilute acids, steam, dilute caustics, petroleum solvents, butane, propane, L.P.G. odorants, etc.

USAGE AND APPLICATION

ATLANTIC No.2 H.D. is designed for use on ball or plug valves that are leaking due to wear or scoring. It is excellent as a thread sealant for standard pipe or coarse threads, packing for stuffing boxes, and a supplementary sealant for valve stems. ATLANTIC No.2 H.D. is pumpable with a valve lubricant high pressure (10,000 psi) gun** such as the ATLANTIC 1010 Hand Gun or the ATLANTIC 1699 Hydraulic Hand Gun.

ADVANTAGES

- M Stop Leaks**
- M Will Not Dry Out**
- M Is Both A Sealant And Lubricant**
- M Broad Serviceability Range**

TYPICAL SPECIFICATIONS

Color Reddish Brown
Texture Viscous and Granular
Base Oil and Thickener Synthetic
Bridging Agent PTFE Fluorocarbon Resin
Service Range 0 F to 500 F
Service Pressure 15,000 PSI

**Caution: Due to the multiple particle sizes of PTFE do not pump with air operated equipment. Not Recommended for Oxygen service.

PACKAGE AVAILABILITY

"J" Sticks (1¼ " x 8½) packaged 16 sticks/carton, 3 carton/case