ATLANTIC ™ TFX-10
PTFE THREAD SEALING COMPOUND

DESCRIPTION

*ATLANTIC TFX-10 is a non-toxic, non-drying thread sealing compound consisting of a blend of non-*melting grease, PTFE particles and other inert solid fillers engineered to produce a leak-proof seal. *ATLANTIC TFX-10 does not contain lead, graphite, molybdenum disulfide, or clay fillers.*

USAGE

ATLANTIC TFX-10 can be used to seal all threaded joints in plastic, aluminum, monel, or stainless steel lines against water, natural gas, LPG, gasoline and other services. It is also effective on connections, pipe bungs, bolts, flange seals, and as a gasket-parting compound.

ADVANTAGES

M CONTAINS PTFE
M PREVENTS CORROSION
M NON-HARDENING
M POSITIVE SEAL
M NON-TOXIC
M HOLDS PRESSURE TO 10,000 PSI (Gases)
3,000 PSI (Liquids)

TYPICAL SPECIFICATIONS

TEST	ASTM METHOD	RESULT
Color	----	White
Usable Temperature Range	(Brushable from +15°F)	-35 to 550+
Specific Gravity	----	1.19
N.L.G.I. Grade	----	1
Penetration	D-217	310-340
Flash Point, F	D-92	400
100 hr., 5% Salt Spray	D-117	No Rust
VOC Content, %		0

CAUTION: DO NOT USE ON OXYGEN SYSTEMS

PACKAGE AVAILABILITY

½ pint brush top jars (packaged 12/case)
1 pint brush top jars (packaged 12/case)
1 gal. Pails, 5 gal. Pails, 15 gal. Kegs, and 55 gal. Drums